




# LÍNEA CONTINUA PLAFÓN

TECNOLOGÍA LED



LÍNEA P16 - P32											
NOMBRE	POT.	LÁMPARA	TIPO	LÚMENES	°K	IRC	FP	MEDIDAS			MODELO
LÍNEA P16	16W	LED T5	INDIVIDUAL	1.280	4.000 / 6.500	>80	>0.5	1200	75	50	35220
	16W	LED T5	CENTRAL	1.280		>80	>0.5	1200	75	50	35221
	16W	LED T5	LAT. CONEX.	1.280		>80	>0.5	1200	75	50	35222
	16W	LED T5	LAT. OPUESTO	1.280		>80	>0.5	1200	75	50	35225
LÍNEA P32	32W	LED T5	INDIVIDUAL	2.560	4.000 / 6.500	>80	>0.5	1200	75	50	35200
	32W	LED T5	CENTRAL	2.560		>80	>0.5	1200	75	50	35223
	32W	LED T5	LAT. CONEX.	2.560		>80	>0.5	1200	75	50	35224
	32W	LED T5	LAT. OPUESTO	2.560		>80	>0.5	1200	75	50	35226

Sistema de iluminación modular colgante con su cuerpo fabricado de aluminio extruido y difusor de policarbonato opal. Con accesorios en acero inoxidable y aluminio. Provisto con LED's con un rendimiento mayor a 90lm/W. Vida útil: 20.000 Hs.

COLORES:

